												1						
	ST	anford	o magn	ETS	.:'			.:'	E	:::			11	.:'	E	n.	.:'	::
1		11	 		··:	• •	1				1			· .			`	
	1 1 1 1	11		1			4						S:	1 - 1 - 1 - 1		Δ	> > di	
1					.:'	<u>,</u> ₽:		a'	E		a'				E		.:'	
		11	1 I 1 I				ON: 1/4"	' X 1/8" X	1/16" THIC	K	1 1 1 1	 			1 I 1 I	r a	NORTH	
	1		Q:"				16		N. Fr			-iv (Ø.3	\geq	
	et.			J) Hi				2/-					2.2				$\geq \odot$.	
		·	1 I 1 I		<u></u>		MAT	ERIAL:		0389	1 1 1	:::	11	•				
	1. 1. 1.			19			DIM		I: 1/4″ X									
	et.			Jet			WEI		ES: ±0.00): 0.008! 2		±0.004"				T		≥ ă	
	1 1 1 1 1	11		1 1 1 1	1. j	• •	ÇOA	TING: N	- NICKEL (E(LBS): 0.		D MAGN	NETS	1	1		1	1. 1.	
	14 14						SURFACE FIELD(GAUSS): 3723 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 1/4″ X 1/8″ MAX OPERATING TEMP(C/F): 80/176 DENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STANDARD MAGNETS											
	•••		4,	· · ,												· · .	at a	
					A 1													