ST	anford	Magr	IETS											ų!		1 	; !
			ja.					2.		111	21.			<u>:</u> :.	.5		1 0 1 1
 :+:	ä		j.	1	:	1		·		::		Se.		;	Д	> ;;	
					<u>↓</u> .;:			ųł.						ų:	1		
.11			.÷-				' X 1/4" X	1/8" THICK		· · ·	:: : :			::. ::.		NORTH	┨ ∷.
	1)'''				14	1				- ir (2ª	* *			2 ::	
 10		스글스	<u> </u>	<u>6</u>	4	<u> </u>						2.0		4	Ą.	2 G	
, i ·			1			MAT	FERIAL:		0465		Н.			Η.			1 . 1 .
 14	н П// (DIM		J: 3/4″ X ES: ±0.00						;		3	
		<u>s</u> t.				WEI	GHT(OZ DE: N42	.): 0.1			X =0.0			· (†			
 .11			.1.		::. ::.	ÇOA	ATING: I	NICKEL (E(LBS): 6.		D MAGN	NETŞ			,÷			
					:	MAG	GNETIZA	ELD(GAU	IRECTI	ON: THF	ROUGH	THICK	NESS			.:	
 	3			PROPRIET		ΜΑΧ		FACE: 3, ATING TE	EMP(C/	F): 80/17					н н Н	.1	
	1.1	1	1.	A 1 1				1						1 1 1			