:	ST	anfori	o magr	ETS		;;;									;		1 1 1	
		te.	14	<u>(</u> 1)	14			' 11			191 191	141		1 1	141			
	- '}-			ji.	1	m	1	- B			Tr (Sy.,		<u>)</u>	Д		
	Det		1		· ; ;	<u>↓</u>		1	· : '		11	· . ·			:	1 1		
	(4)	19 19		19			ION: 3/4'		1/16" THIC		14 14				14		NORTH	
	4		्राः				16	Ŷ	N. II.			-in (Qi.					
	14		그같이	U) Te	<u>0.</u>].)/	44		24			H V	~~? }	2		4		è.	
	(4) 	÷.,	14	11	14 14		MAT	ERIAL:		0468	14 1		<u></u> 11	· .	14		' 4	
	1	н. П 27 - Л				:	DIM		оск I: 3/4″ X ES: ±0.00									
		'P	Č.T.				WE		.): 0.076		±0.004	⊼ ±0.0			1		×.	1
	<u>(</u> 1)	1	11	<u>]</u> 1-	19 19		COA	TING: I	- NICKEL (E(LBS): 3		D MAGN	NETS	1 1	·		1 1	1 1	
	- '}-			1		:	MAC	GNETIZA	ELD(GAI	IRECTI	ON: THF	ROUGH	THICK	NESS	111	;		
:	: . : .	1	1			ARY AND CONFI	MAX	(OPER/	FACE: 3	EMP(C/	F): 80/17						• • •	1
		·			A						·			•			·	