	ST	anforc	magn	ETS			:.'		:	'			: · *		:	p'	`; `	
	3		÷.	31		Ŀ.			÷.			÷.	1		÷.		· · · ·	· .
	14			Ja		:							She.		<u></u>	Д	> > 8	
	et.			::'	:	, ↓ _:`		1										
	1 1 1 - 1 - 1 - 1	•	÷.	1 1 1 1 1			ON: 3/4″	X 3/4" X	1/4″ THICK	r 	·	ŀ.			ŀ.		NORTH	
		a	@!"				1		N. Fr		75.7		<u></u>			PR	2 m	
1	et.					4 <i>6</i>							$\mathbb{Z}_{\mathbb{Z}}$		Ì		è q.	
			ŀ.			÷.	MAT	ERIAL:		10485		ŀ.	11		ŀ.			· .
			:				DIM		DCK J: 3/4" X ES: ±0.00								 	
			i i				WEI		.): 0.61		±0.004				T			1
	1 1 1 1 1			1 1 1 1 1		÷.,	COA PULI	TING: N _ FORCI	NICKEL (E(LBS): 2	1.94		NETS	н н н		···.		1 - 1 1	
			:	•		:	MAC	GNETIZA	ELD(GAI	IRECTI		ROUGH	THICK	NESS				
		1	:		PROPRIET	ARY AND CONFI	MAX	(OPERA	FACE: 3	EMP(C/	'F): 80/17				1		1	
					A 1 1			i it						÷ .				