PRODUCT ID: SMBN0519 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 1" X 1/2" X 1/4" THICK PRODUCT ID: SMBN0519 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 1" X 1/2" X 1/4" THICK TOLERANCES: ±0.004" X ±0.004" WEIGHT(02): 0.54 GRADE: N52 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 25.22 SURFACE FIELD(GAUSS): 4174 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 1" X 1/2" MAX OPERATING TEMP(C/F): 80/176								1.						1.			
PRODUCT ID: SMBN0519 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 1" X 1/2" X 1/4" THICK PRODUCT ID: SMBN0519 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 1" X 1/2" X 1/4" THICK DIMENSION: 1" X 1/2" X 1/4" THICK A A A A A A A A A A A A A A A A A A A	ST	апгояс	magn	ETS			, P			.11						.27	
PRODUCT ID: SMBN0519 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 1" X 1/2" X 1/4" THICK MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 1" X 1/2" X 1/4" THICK TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 0.54 GRADE: N52 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 25.22 SURFACE FIELD(GAUSS): 4174 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 1" X 1/2"	e.	11.	E.	21	1.	11	1 I I 1 1				Ч.		11				11
PRODUCT ID: SMBN0519 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 1" X 1/2" X 1/4" THICK TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 0.54 GRADE: N52 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 25.22 SURFACE FIELD(GAUSS): 4174 MAGNETIC FACE: 1" X 1/2" MAY OUTPATING THICKNESS MAGNETIC FACE: 1" X 1/2"	·		Q	·		:			<u>у</u> р.				S		i	$\Delta$	> ~ 1:
PRODUCT ID: SMBN0519 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 1" X 1/2" X 1/4" THICK TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 0.54 GRADE: N52 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 25.22 SURFACE FIELD(GAUSS): 4174 MAGNETIC FACE: 1" X 1/2" MAY OUTPATING THICKNESS MAGNETIC FACE: 1" X 1/2"																	< 0 .:!
PRODUCT ID: SMBN0519 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 1" X 1/2" X 1/4" THICK TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 0.54 GRADE: N52 COATING: NICKEL COATED MAGNETS. PULL FORCE(LBS): 25.22 SURFACE FIELD(GAUSS): 4174 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 1" X 1/2" MAS OPERATION TEMPO(CID: \$0/174						DIMENSI	ON: 1" >	( 1/2" X 1/4	4″ THICK								
PRODUCT ID: SMBN0519 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 1" X 1/2" X 1/4" THICK TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 0.54 GRADE: N52 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 25.22 SURFACE FIELD(GAUSS): 4174 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIZATION DIRECTION: THROUGH THICKNESS	.'			.'	:		.'		11.	.'	1.	11.			11.		NORTH
PRODUCT ID: SMBN0519 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 1" X 1/2" X 1/4" THICK TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 0.54 GRADE: N52 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 25.22 SURFACE FIELD(GAUSS): 4174 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 1" X 1/2" MAX OPERATING TEMP/C (E): 90/174	·	Ξ.	Q:''	•		17	1.1	11	The second			-ir (	Q			<u>_</u>	≥ ::
MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 1" X 1/2" X 1/4" THICK TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 0.54 GRADE: N52 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 25.22 SURFACE FIELD(GAUSS): 4174 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 1" X 1/2" MAX OPERATING TEMPIC (7): 90/174											at N		$\mathbb{P}_{q}$				2 9
DIMENSION: 1" X 1/2" X 1/4" THICK TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 0.54 GRADE: N52 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 25.22 SURFACE FIELD(GAUSS): 4174 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 1" X 1/2" MAX OPERATING TEMP(C (E): 90/174			: :			:-:	MAT	FERIAL: I	NDFEB	0519	1.		11				Έ.
WEIGHT(OZ.): 0.54 GRADE: N52 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 25.22 SURFACE FIELD(GAUSS): 4174 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 1″ X 1/2″	<b>'</b>			·		;	DIM	ENSION	l: 1″ :X 1/							·	
COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 25.22 SURFACE FIELD(GAUSS): 4174 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 1″ X 1/2″ MAX OPERATING TEMP(C (F): 80(174)	1	đ					WEI	GHT(OZ	.): 0.54						λ.		2 8
MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 1″ X 1/2″ MAX_OPERATING_TEMP(C/T): 80/176	· · · · ·				1		COA	ATING: N		1	D MAGN	IETS	1 1 1		'		1
	<b>'</b>	1 - 1 - 1 - 1 - 1	:	·		:	MAG	GNETIZA	ATION D	IRECTI	ON: THR	ROUGH	THICK	NESŞ	:	1	н н н
PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STANDARD MAGNETS	.:				. • •		MAX	K OPERA		EMP(C/	F): 80/17						