STE	INFORD	Magn	ETS											·:•		1 	-
	а <u>.</u>		ġ.	н. Т		÷.	9.	::		÷.,	::		1.	::	÷.	1.	
	4 ( ) 14 ( )	) av			<u></u>	'				- 17 (		Syr,		<u>.</u>	Д	> > #	
		· ; *	11		, <b>i</b>				11					4	1		t.
					DIMENSI			( 1/4" THIC									
			: .				÷.,	1 I 1 I		i.,					-	NORTH	
		):"			-	11	T	N Pr		11	- in (	S.			(7) 	25	
			10) 11:11		11 <i>L</i> <sub>i</sub> -						그같	21:0				è g.	
	5.		÷.	÷.,	:::	MA	DUCT II FERIAL:   PE: BLC		0557	÷.,	 		÷.,	 	đ.	5.	
					:	DIM	ENSION	l: 1 1/2″						;			
	V ( )	2.			<u>۱</u>		ERANCI GHT(OZ	ES: ±0.00						N.,		2	
		1					DE: N42							1		$\geq 0$	
	1.	1 - 1 1 - 1	÷.	÷.,	1 - 1 1 - 1	1.1	1	NICKEL ( E(LBS): 3	1.1		NETS	· · .	· · .	1 - 1 1	11. 1		- - - -
								ELD(GA									
								ATION D FACE: 1			ROUGH	IHICKI	NESS		1		
:	1	'	1	PROPRIET	ARY AND CONFIL	MAX		ATING T	EMP(C/	F): 80/17					1	.:	: '
1	1			A ; .										1 1 4 4			