PRODUCT ID: SMEN0560 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 3/4" LENGTH X 1 1/2" WIDTH X 3/8" THICK MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 3/4" LENGTH X 1 1/2" WIDTH X 3/8" THICK , WITH STEP IN TOLERANCES: ±0.004" X ±0.004" WEIGHTICZ, 1: 73 GRADE: N42 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 43.51 SURFACE FIELD(GAUSS): 3839 MAGNETIC FACE: 3/4" LENGTH X 1 1/2" WIDTH	. 11	1		. 11							11	1				. 11	11	
PRODUCT ID: SMBN0560 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 3/4" LENGTH X 1 1/2" WIDTH X 3/8" THICK , WITH STEP IN TOLERANCES: ±0.004" X ±0.004" WEIGHT(02.): 1.73 GRADE: N42 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 43.51 SURFACE FIELD(GAUSS): 3839 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 3/4" LENGTH X 1 1/2" WIDTH	ST	anford	Magr	IETS	'							·::					.:'	
PRODUCT ID: SMBN0560 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 3/4" LENGTH X 1 1/2" WIDTH X 3/8" THICK , WITH STEP IN TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 1.73 GRADE: N42 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 43.51 SURFACE FIELD(GAUSS): 3839 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIZATION DIRECTION: THROUGH THICKNESS		*•.		11	<u>.</u>	• •		` ',		 	<u>5.</u>	1 1 1 1	11	÷.,				
PRODUCT ID: SMBN0560 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 3/4" LENGTH X 1 1/2" WIDTH X 3/8" THICK , WITH STEP IN TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 1.73 GRADE: N42 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 43.51 SURFACE FIELD(GAUSS): 3839 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 3/4" LENGTH X 1 1/2" WIDTH MAX OPERATING TEMP(C/F): 50/175	le:	N.	4"	j.				<u>'</u> r	<u>_</u>		- 11 (Sep	1 1 1	\. 	Ą	> > di	
PRODUCT ID: SMBN0560 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 3/4" LENGTH X 1 1/2" WIDTH X 3/8" THICK , WITH STEP IN TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 1.73 GRADE: N42 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 43.51 SURFACE FIELD(GAUSS): 3839 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 3/4" LENGTH X 1 1/2" WIDTH		1				<u> </u>					a'						.:'	
PRODUCT ID: SMBN0560 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 3/4" LENGTH X 1 1/2" WIDTH X 3/8" THICK , WITH STEP IN TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 1.73 GRADE: N42 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 43.51 SURFACE FIELD(GAUSS): 3839 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 3/4" LENGTH X 1 1/2" WIDTH MACOPERATING TEMPSC/T18 20/176		÷.,			· .			LENGTH	X 1 1/2" WI	DTH X 3/	8″ THICK						NORTH	
PRODUCT ID: SMBN0560 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 3/4" LENGTH X 1 1/2" WIDTH X 3/8" THICK , WITH STEP IN TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 1.73 GRADE: N42 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 43.51 SURFACE FIELD(GAUSS): 3839 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 3/4" LENGTH X 1 1/2" WIDTH MACOPERATING TEMPSC/T18 20/176						↑ - -							\checkmark					
PRODUCT ID: SMBN0560 MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 3/4" LENGTH X 1 1/2" WIDTH X 3/8" THICK , WITH STEP IN TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 1.73 GRADE: N42 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 43.51 SURFACE FIELD(GAUSS): 3839 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 3/4" LENGTH X 1 1/2" WIDTH MAX OPERATING TEMP(C/F): 80/176	1 te	je (11	1	:**		1			11	(r)		111		(in)	> ' <u>1</u> -	
MATERIAL: NDFEB SHAPE: BLOCK DIMENSION: 3/4" LENGTH X 1 1/2" WIDTH X 3/8" THICK , WITH STEP IN TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 1.73 GRADE: N42 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 43.51 SURFACE FIELD(GAUSS): 3839 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 3/4" LENGTH X 1 1/2" WIDTH MAX OPERATING TEMP(C/F): 80/176	at i					44 19	4,2						Z:8			S.S.) T	t.
DIMENSION: 3/4" LENGTH X 1 1/2" WIDTH X 3/8" THICK , WITH STEP IN TOLERANCES: ±0.004" X ±0.004" WEIGHT(OZ.): 1.73 GRADE: N42 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 43.51 SURFACE FIELD(GAUSS): 3839 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 3/4" LENGTH X 1 1/2" WIDTH MAX OPERATING TEMP(C/F): 8C/176					· .		MAT	ERIAL:	NDFEB	0560	<u>'</u> .	1 - 1 1 - 1			1 1 1 1		· .	
WEIGHT(OZ.): 1.73 GRADE: N42 COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 43.51 SURFACE FIELD(GAUSS): 3839 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 3/4″ LENGTH X 1 1/2″ WIDTH MAX OPERATING TEMP(C/F): 80/176	 	• •		te.		:	DIM	ENSION	I: 3/4″ LI			' WIDTH	H X 3/8'	' THICK	, WITH S	STEP IN	J : <u>;</u> ,	
COATING: NICKEL COATED MAGNETS PULL FORCE(LBS): 43.51 SURFACE FIELD(GAUSS): 3839 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 3/4″ LENGTH X 1 1/2″ WIDTH MAX OPERATING TEMP(C/F): 80/176			S at a			1 <u>.</u>	WEI	GHT(OZ	.): 1.73				Set,			('	> ਰੱ	
SURFACE FIELD(GAUSS): 3839 MAGNETIZATION DIRECTION: THROUGH THICKNESS MAGNETIC FACE: 3/4″ LENGTH X 1 1/2″ WIDTH MAX OPERATING TEMP(C/F): 80/176		1.			5	1 i	ÇOA	TING: N			D MAGN	IETS	• •	1	н н н			
MAGNETIC FACE: 3/4" LENGTH X 1 1/2" WIDTH MAX OPERATING TEMP(C/F): 80/176	1	·		•			SUR	FACE FI	ELD(GA	JSS): 38		ดบุติษ	ТНІСКІ					
			,															
			· · .															