	1			1.			1.			1.							
STa	INFORD	Magn	ETS						:::		· ; '						
2			j.														
1.1	*e.					1				- (1.	10	Д		
et.	ai i				<u>_</u> `						• ; '			·;*			
	• • • • •	÷.,					X 1″ X 1/4″ ∷∵:	THICK	11	1 - 1 1 - 1 1 - 1	÷					NORTH	
<u>.</u>	147 (Q):"	:.: :::		-	1				76.7	-1º (Q#		1	<u> </u>	>	
21		고급이	U) et		4.		2/	<u>.</u>				94:17				201	
111		:.		1 1 1 1	: 	MAT	DUCT II FERIAL: PE: BLC		10594		÷.,	11					
	• 	;				DIM	ENSION	J: 2″∶X 1 ES: ±0.00						;		':. S	
ni.		S d'	je:			WEI	GHT(OZ DE: N4	.): 2.17						1		2 0	
	141		- 1 - 1 - 1 - 1 - 1			PUL	L FORCI	NICKEL (E(LBS): 3	6.07	1	NETS ,			1.			
<u>.</u>	• 1.	;	14	'	:	MAG	GNETIZA	ELD(GA ATION D FACE: 2	IRECTI		ROUGH	THICKI	NESŞ	111		14. 1	
· · .	19	*	11	PROPRIE	TARY AND CONFI	MAX		ATING T	EMP(C/						11		
				A r - r													