1	ST	anfori	o magn	ETS								1.1						
• :	.:	::: 		.:	i:	11	.:		:-:	.:					ie.	.:		:
		άę.		Ja.	:::	:			÷				Se	1.		Δ	् २ हे	
				11			141											
							ON: 3" X	(1/2" X 1/ (8" THICK	.:					11		NORTH	
	1		Q!"			1 :2	1	1.	N.Fr		- 1. 1	-Dr (Q.	i.	÷	Q.	⊃ _{tir}	
	1. t							2					242				≥ 0	1 1 1 1 1
';	.:			.:			MAT	DUCT II ERIAL: PE: BLC		10613		11	.:		in.	.:		
				1			DIM	ENSION	J: 3″:X 1/ ES: ±0.00							·1.	S lie	
1							WEI		.): 0.81						Ē		े हैं	
1	.:		1 1 1 1	.1			PUL	L FORCI	NICKEL (E(LBS): 1	8.33		NETS	:			1		
						;**	MAC	GNETIZA	ELD(GA) ATION D FACE: 3	IRECTI	ON: THF	ROUGH	ТНІСКІ	NEŞS	;			
		. :	4,	• •	PROPRIET	ARY AND CONFIL	ΜΑΧ		ATING TI	EMP(C/	′F): 80/17		STANDARD M	AGNETS	4			
					A													