	i.	i l	111	1'1			ı'r		1 1 1	π'i	i .			x"		1.1	i i	
ť	ST	anford	Magn	ETS						· · · • ·			· · ·	14				
E E E 1		.1:	1	ţ.,	.4									.ii				1.
						_ φ	DIMENS	ion: 1/16"	DIA. X 1/1	6" THICK								
u.			1			111	, ^{, ,}	<u>,</u>	$\{ c : c \in [0, 1] \}$	2		1			Įα			
			91	· · ·		5	r i T T		11	с. т С. т		1) ¹⁴		· · · i · i		a.
	<u>.</u>	, i j		<u>.</u>	, i		ţ.	.i.;	1.	<u>.</u>	,ii	1.		J.A		11	, i j	1.
I	.et	R	:		NORTH							95						
'			1		A	;, [,]		1.1										
	<u>.</u>			ļo	,÷:	11.	MA	ODUCT I TERIAL: APE: CYI	NDFEB	N0252			ţ.					
	.:		;···			:	DIN		N: 1/16″	1. 1				1d	:			
			5	r r K r		5	1 1	IGHT(OZ ADE: N5	1	083		Ч.	, , , ,		1		1 - 1 - 1 - 1 - 1	
	<u>.</u>	.e	1.	ţ	.÷:	Ч.	PUI	ATING: LL FORC RFACE F	E(LBS): (0.12		NETS		÷.	Ч. М.		4,	
			:			111	MA	GNETIZ	ATION [DIRECT	ION: TH	ROUGH	THICK	NESS	:**			
		5	'	:	PROPRIETAR	Y AND CONFIL		X OPER							*		1	
		i c	1 I I I I		i i			, i i	1 1 1 1			1		, i i				