				1.1	, '		1.1	T		n i i	<i>1</i>		i i i	x'		i i	· · ·	
i L	ST	anford	magni	ETS	:1	11			' 11	: - č		1 1	:-:	r)		et.	:::	
:	i.	.10	1	• **		1							`			·	, in	÷
						$/ \phi$	DIMENS	ION: 1/16"	DIA. X 3/8	" ТНІСК								
C.			1	.11		<u>.</u>	.::		1					'		.::	, ¹	
	:::	1 1 1 1 1					÷,		'E	a d		11		$\mathbf{y}_{\mathrm{eff}}$:::		
1	' <u>'</u> '		1	۰ŗ.	, i i	ł	1		1	';·	, i •	l			1	, i.	, in	1
	.::			<u>.</u>	NORTH										G		, ^{(*}	
E.	11		1	11	· A	':: Г	'	:				11	11		1	:-1		
1 1 1	' 9	. ^{i.}	;	т р		:	MA	DDUCT I TERIAL: APE: CYI		N0257	, i .		ʻ	, ^{is}	1	' !'	. ¹¹	
	11	.e ⁶	:			:	DIN	IENSIO			3/8″ THIC ±0.004″	CK		'	111		e.	
ľ.	el.		1	e.	;;}	11	WE		Z.): 0.005		 	11	e.			a f		
-	':·		1	÷		1	PUI	L FORC	NICKEL E(LBS): (IELD(GA).19	D MAGN	ETŞ			1		, i	-
				;	. '		MA	GNETIZ		DIRECT	ION: THR	OUGH	THICK	NESS			. '	
				*	PROPRIETARY	AND CONFIL	MA	X OPER	ATING T	EMP(C	/F): 80/17 NG IS THE SOLE PR					*		
								, is										