6 1.1. C			111	1		1	1.1		111	1.1		111		2		11		
	ST	anford	o magn	IETS		1				, 				11				÷
	194	.4	· · · · 	÷											1 I I I I I	÷.		1 1 1 1 1
						φ	DIMENS	ion: 1/8" [DIA. X 1″ T	HICK								
	.:1		1	.:1			. : ;	2* ¹	1		p^{\dagger}			21	1	.::		
	, , ,	 		, , ,		1	r X T			a a b			·					
	' }-	, e)		· [.	,		*) <u>.</u>			1						' [i	.4	
ū	t	et.			NORTH	<u>[</u>]./]						38			G	.:.	eć.	
	. :				÷.	÷.							. :					1
	1			<u>'</u>	, ²	TE I	MA	ODUCT I TERIAL: APE: CYL	NDFEB	N0281		Т	ʻį.			Έ.		й н й т й т
		Г 1 П 1 — 1					, DIN		N: 1/8″ C		" THICK :0.004"							
ł						1	Ψ	IGHT(OZ ADE: N4	Z.): 0.053			1	. :	1.3 85	i i			
	4.			3 <u>1</u> 1			PUI	LL FORC	E(LBS): ().89		IETS				:		
e e	e e la composition de	11	111	e ^r	99. 19	;	MA	RFACE F GNETIZ GNETIC	ΑΤΙΟΝ [DIRECT	ION: THR	ROUGH	THICK	NESS		:	··.	
			-		PROPRIETAR	Y AND CONFIL					/F): 80/17 NG IS THE SOLE PP		TANDARD M				1	:
			1 1 1 1 1 1			1 1 1	1		1 1 1 I I 1			1.1.1	1		1.1	1.1	Contraction of the local	