						ŤŤ	1	111	T I			7 F	1	1	1 I 1 I		:
ST	гапгояо	Magn	ETS	11			1			.::					. :		
1.4	.4		14	.4		2.1			<u>.</u>	.÷:		<u>.</u>	.e		1.1	1 1.1 1.1	1
					φ	DIMENS	ion: 2/10"	DIA. X 1/4	" THICK								
· *		1	· 1		11	· 1 1 ·		[**	· 3 X 1		1	r i Ç i		[^{CL}	· 1	c C	
						, , ,	i a i i i		, 			Ċ				i i Ti T	1
ţs.	,i,	1	ţ	, i 1	1	ţ.i	يغ	Т	ţ.	, i ;						, i j	1
- 1 1 1	14			NORTH							98				1 1 3 1		
. :				4													
ļ.	.H	1	ţú	, i :	1	MA	ODUCT I TERIAL: APE: CYI	NDFEB	V0298	, i i		<u>[</u> 11	,iii		<u>1</u> 1	, i i	;
		;		1 1 1 1	;	DIN	/ENSIOI LERANC	N: 2/10″					21		· · ·		
, ;				111	* · ·	, WE	IGHT(O ADE: N4	Z.): 0,.034							, , ,	i i i i i	1.
1.1		1	÷.		1		ATING: LL FORC			D MAG	NETŞ		÷.,	1			
		: · ·			111	MA	RFACE F GNETIZ GNETIC	ΑΤΙΟΝ [DIRECT	ION: TH	ROUGH	THICK	NESS	111	•		
-				PROPRIETAR	Y AND CONFI	MA	X OPER	ATING T	EMP(C	/F): _[80/1		TANDARD M	AGNETS	. :			
	.i.			, i j		1.1		1	10							I I I I I I I I I I I I I I I I I I I	