	1.1						1	111	1 1 1 1 1				x.	111			
S	тапгово	magn	ETS		Ъ.			`;`	2		<u>'</u>		21	C. C		i i i c i c	
14	.is	;	14	.i.	:	<u>.</u>		1	<u>.</u>		:	<u>.</u>	.1.		1.1	. i .	:
					_φ	DIMENS	ION: 1/4"	DIA. X 1″ T	ніск								
	\mathbb{R}^{2}	l.,	 		11			1^{ii}]		ļ.,			10	;•]	(a)	
		Ъ.	x' 1		1			i.	- 1	: ·]	11	Ċ	\mathbf{b}^{el}			1. 1. * 1. 1. *	÷
14	.10	ł		,i.	ł	50	,ii	ł	ļei	.11	1			1	ţei	.i.	:
1	1.1			NORTH	···/			i			983					14	
	:::			: 🐴	· ; ·			`.``		:::	1		:::	`;;`		::1	1
ļ.		ł	14	,;, ,;,	:	MA	DDUCT I TERIAL: APE: CYI		N0315	, i .	;	<u>.</u>					;
	11					DIN	IEŅSIOI			" THICK ±0.004"	111		11				
. :		ст. С			1		IGHT(OZ ADE: N4		÷		<u>'</u> 1'			ſ		i i	1
<u>.</u>	.**	}	1 ,	,i.			ан (т. с.	NICKEL E(LBS): 4			NETS		.1	:		.:	
	1	:		1	:	MA	GNETIZ	IELD(GA ATION [FACE: ⁻	DIRECT	ION: THF	ROUGH	тніск	NESS			'	
	···.	1		PROPRIETAR	Y AND CONFI	MA	X OPER	ATING T	EMP(C	/F): 80/17 NG IS THE SOLE PI		STANDARD MA		:		···,	
1.1			11	, i c					ļd	, i i					14	C C	