1.1	i i	111	a'a			ŤŤ		111				r' r			a 'a		
ST	anford	Magn	ETS		÷				.3	11	:	.::		÷.	.::		
ţ.		1.	14	.4		1.1					1 H H H H				1.1		1.
					φ	DIMENS	5ION: 3/16"	DIA. X 1/3	32" THICK								
.::		1			111	, : : , : :	<u>,</u>	1			1			Įα			
.::		÷.	1 1 1 1		i.			i.			۱ <u>۰</u>		$\mathbf{y}_{\mathrm{res}}$	1	.11		
<u>.</u>	.4		<u>.</u>	,		11	.++	1.					Jui		<u>.</u>	.4	1.
.1		:		NORTH	* **						95			G	.::		
. ::		1		÷ ф	÷	_					i pr	.::		1	.::		1.
<u>.</u>			ţ	,.	11.	MA	ODUCT I TERIAL: APE: DIS	NDFEB		, tİ	1.	ţ.:		1.	11		
		;···		:	:	DIN		N: 3/16″		1/32" TH ±0.004"	HICK			:··			
.:	1 - 1 1 - 1	÷			÷1.	WE	IGHT(OZ ADE: N5	Z.): 0.003		i k T	÷.	.::		:	.::	r i F f	1.
1 1 1 1 1		1.	<u>.</u>		1.	CO PUI		NICKEL E(LBS): (0.43		NETS			÷.,			
.:		:			;**	MA		ATION D	DIRECT	ION: TH	ROUGH	THICK	NESS	: • •			
	14. 14.		1	PROPRIETAR						/F): 80/1 NG IS THE SOLE F		TANDARD M/			1	14. 1	
<u></u>						11				i i	· .					1	