ι'i	.'		11			1 1			r'i	, '		1 i			a 'a	.'	
ST	anford	magn	ETS			, 1 , 1 , 1	:::	::·	r.			:::	r:	i.	11		1
;			ţ.			1.1			ļ.			<u>.</u>			<u>.</u>		1 1 1 1
					_φ	DIMENS	ion: 5/16"	DIA. X 1/3	32" THICK								
.1			. :		11	. : :			23	, e*	;		'	111	.9	. · ·	
ri.					3	ı.i	el.	Ξ.	ari.	i			\mathbf{z}^{el}	T	a di		
ţ.			<u>.</u>	, i ·			.i•		<u>1</u> 1	,it			a la		ţ.		- 1 - 1 1 2 2
.:	⁴	:		NORTH	:/									G	. : :	e ^r	
:-1			:-1	: 4	iai [:		el.			:::			et.		
ļ	.i+			, i ·		MA		NDFEB	N0040	di	11	<u>1</u> 4	÷		ţa	.i.	
	.2	:				DIN	APE: DIS /IENSIOI LERANC	N: 5/16″				.::	.'	;	.8	e.	
11			÷.				IGHT(OZ ADE: N5		e.		11				11		
<u>.</u>			ţ.:			CO	ATING: LL FORC	NICKEL		D MAGI	NETS			1 - 1 1		:	
1			.:			MA	RFACE F GNETIZ	ATION I	DIRECT	ION: TH	ROUGH	THICK	NESS	;···	j.		
'			*		Y AND CONFI	MA		ATING 1	EMP(C	/F): 80/1					'		
54	, i c							· · · · · · · · · · · · · · · · · · ·	10								