	, li	1		1		111			1	τί	1	111	e i e	i. I				
	ST	апгояр	magn	ETS						.4			. 1	.4	С.		e e	1.
	te.	11		÷.	11	Ŀ						1.						1.
						_ φ	DIMENS	510N: 3/8″ [	DIA. X 1/16	5" THICK								
		: * <sup>*</sup>	l.,		(	111		:• <b>`</b>	$\{ r \}$		$e^{i}$	1.1		$2^2$	l cr			
	. 1		1.	, 1 1 - 1		1.	, - <u> </u>	. 'r	1.	. :	.1	Έ.	Č				 	1.
	÷.	į d	1.	*.i	1.1	I.	<u>'</u> ;i	į i		' <u>ң</u>	111	I.				5	;+i	1.
		et'		<u>_</u> .:	NORTH										Œ		e <sup>r</sup>	
	1		*i.	. · · ·		°Е. –	-		1.		. :		]	. 1		!		
	<u>'</u>	1 <sup>11</sup>	<u>.</u>	÷	;••		MA	ODUCT I TERIAL: APE: DIS	NDFEB	N0052	i <sup>11</sup>		ţ	2 <sup>11</sup>		19	i	
	.:1	ef.	;			;	DIN	AFE: DIS MENSION LERANC	N: 3/8″ E				.::	er'		.::	ef.	
	.1		1.	r'r r'r		1.		IGHT(OZ ADE: N4				1.	.1	a s			r í	1.
	'+÷		ł.,				PUI	ATING: I LL FORC	E(LBS): 2	2.12		NETS	:	'	Ξ.	ť		
	:			:			MA	RFACE F GNETIZ	ΑΤΙΟΝ [	DIRECT	ION: TH	ROUGH	THICK	NESS		af i		
-			1		PROPRIETAR	Y AND CONFID	MA		ATING T	EMP(C	/F): 80/1		TANDARD MA		Ξ.			
L	Ţ.	i Ci	1.		i i i	1	111	i.i.	1	ţ.	i. i	1	i i	ini -	1			