(- 1.5) (11			a a	1		1 ¹ 1	÷.,		τ'i	÷.,		r' r	<i></i>		a 'a	1	, , ,
	, st	anford	o magn	ETS									. :					
1	1.0	.4	1		ja -		;··		1	<u>.</u>	, · i	1	<u>.</u>			ţ	. · i	-
						_ φ	DIMENS	ION: 1/2" [DIA. X 1/32	" THICK								
		:* [*]	1	. :	(21 [°]	$\{ c : c \in [0, 1] \}$	<u>, 1</u>	(**	1.1	e e	x'	1		;•*	
	.4		11			10			11			11	Ċ					:
	<u>;</u>	, ci		<u>,</u>	, ii	1	<u>(</u>	i		-0					1	ţ.,	i	1
	:	e'			NORTH		4		1				0				e ^r	
	.1				÷ A	'i: Г	:			.:1					с. Г.	!		1.
	ţ.					1	MA	DDUCT I TERIAL:	NDFEB	N0081	[.]			i		ţ.	, ii	1
	:	: '			, I		DIN	APE: DIS IENSION LERANC	N: 1/2″ E				.::	: ¹			et.	
i i	.1		11	. :		11		IGHT(OZ ADE: N4		7						.:1		
	<u>.</u>			ļ			PUI	ATING: L FORC	E(LBS): ²	1.15		NETS		. '				1
		¹			¹		MA	RFACE F .GNETIZ. .GNETIC	ΑΤΙΟΝ [DIRECT	ION: TH	ROUGH	THICK	NESS				
с (К		1		.**	PROPRIETAR	Y AND CONFID	MA		ATING T	EMP(C	/F): _: 80/1						1	
		e ^{t i}	1 1		, ¹¹	1	ļu	. ¹¹	1					a ^{ri}			i i i	