		1 1 1	1 1		1	1 1	1	111	1.1	ĩ.,	111		1 . 1	111		î.	
ST	апгояс	magn	ETS	1						.::			.1			e e	
ie.	16	÷	1e	19		·	1 1 1		т. 1			`			·	1 1 1 1 1	1
					_ φ	DIMENS	ION: 9/16"	DIA. X 2/1	о" тніск								
.1	.11	1				x i r	1	[ **		, i (	1		. (†	Įα		$e^{\frac{1}{2}}$	
						1 - 1 1			.1	.11		Č				 	
`;·	19	.l·	·	19	.þ	'e	19	.1.	1	le.	. F				'p	le.	ŀ
.::	.8			NORTH	···/			1.1			95	.:: (7				.e.	
.1					Тя: Г	:											
<b>`</b> !'	10	.†°	Ţ		.1	MA	ODUCT I TERIAL: APE: DIS	NDFEB	N0110	ie.			T		,		8 8 1 1
	.8	;···			:	DIN	/ENSION	N: 9/16″					.8	;···		.8	
. 1				.::		WE	IGHT(OZ ADE: N4	Z.): 0,22				.:					
	le:	.H	÷	1e	÷	PU	ATING: LL FORC RFACE F	E(LBS): 1	1.39		NETS	1					
1	1	111	1	4,	: · ·	MA			DIRECT	ION: TH	ROUGH	THICK	NESS	:**		1	
	.1		. • •	PROPRIETAR		MA		ATING T	EMP(C	/F): 80/1		TANDARD MA				2	
		1 1 1 1		, i i			- 	1 1 1 1	1 1 1	. I I I I							