1.1			1 1			x ' x		1	τ' τ		, , ,	x 1		L L L			
ST	anford	magn	ETS		1.	111			11	.::	1.	11	.1	L) L)			1
:.:	1		÷:			:.:			1 1	. · ·							1
					_ φ	DIMENS	ION: 5/8" [DIA. X 1/4"	THICK								
, · ;	.**	<u></u>				x ¹	. 1	[* *	$\frac{1}{2}$	x ^{1*}	;			111	. 1	. ¹¹	
		Ч.,	i a ala		÷.	 				.::	1.						1
5.			* . : • . :	ļ											53		1
	, ¹¹	:		NORTH	:/					."	35			G		, ¹¹	
1 8 1 1 1	.::	*\		ب	Ч. Г	_ ::				.::	Π.			1. 1. 1.			
6.1	<u>]</u>		1.1		-1.	MA	DDUCT I TERIAL:	NDFEB	N0125	<u>.</u>		:.:	<u>.</u>		1.1		
			.:	. : 1		DIN	APE: DIS IENSION LERANC	N: 5/8″ [
	r i r	Έ.		.8	1.	WE	IGHT(OZ ADE: N5	2.): 0.33	 		1.					$\frac{1}{1-\epsilon}$	
1.1		- 1 - 1 - 1			4.	, ÇO	ATING: L FORC	NICKEL		D MAGI	NETS	¹	1	· · · .	'	5	
	.÷			j)		MA	RFACE F GNETIZ	ATION [DIRECT	ION: TH	ROUGH	THICK	NESS	1 1 1 1		.)÷	
			1	PROPRIETAR	Y AND CONFI	MA		ATING T	EMP(C	/F): 80/1		STANDARD M	AGNETS		1		