			1 1 1				1			T I		111	i i i	. '.	1			
	ST	апгояр	magr	IETS	:	1		21		· · · • ·		1		11			r.	1
10 1 10 10	:	.4		<u>.</u>	.4					<u>.</u>								1 1
						_ φ	DIMENS	ION: 5/8" C	DIA. X 1/2"	THICK								
	1 - 1 - 1 2 - 1	, s.	1			- F-			{**		. · .	1		2	Į ci	1.1	, s ¹	
	::	el.	1	· 1 7 7			 		1	· •	et.	1		\mathbf{y}^{sd}	Ч		r.	
	<u>;</u> 0	, i j	.T	<u>.</u>	, i		<u>i</u> co	, i j		<u>.</u>	,i,			J., ³ t		ţ.	, ¹)	
	14	2	:		NORTH							95	 (7				.e.	
			1		: 🐴	·;			1		:::	1					::1	
	<u>.</u>	, i i			,;	.1	MA	ODUCT II TERIAL: APE: DIS	NDFEB	N0127	÷		ţ.	,ii				й н 1
		.d				:	DIN	IENSION LERANC	N: 5/8″ [СК :::		.et	;···			
			1			1	1 I	IGHT(OZ ADE: N4		· · · · ·	n.	Ϊ.		al i	1		rî.	1
	<u>.</u>	.÷:		1.	.÷:		ÇO PUI	ATING: I LL FORC	NICKEL E(LBS): 2	22.6		NETS		÷.				- - - -
	1	.:	;··	5	.:	111	MA	RFACE F GNETIZ GNETIC	ΑΤΙΟΝ Ι	DIRECT	ION; THI	ROUGH	THICK	NESS	111	5		
	· · ·	11. 1	}		PROPRIETAR	Y AND CONFID		X OPERA			1			AGNETS			···.	
Ê				10	i.			i.		ļo	, i ;	.1		, it			, È ,	