1	ĩ		1 1	1		ï'ĩ	1	1 1 1	τ΄i	1	111	î î		1			
ST	апгояс	magn	ETS		5					.::			2 2				
		.:	·	le.		`	1 1 1		۰. ب						·		
					_ φ	DIMENS	510N: 3/4" [DIA. X 1/8″	ТНІСК								
		l.,			11			[**	1 - 1 3 - 1	, ¹⁴	1	r r c'r	.27	{ ca		e ^t	
		1) ¹	1 1 1 1 1 1		: j. '				;-::		1)		1.1		
'р	19	.]	·	(n	.1	, i i	19		,'n	ļ.					'p		
11	, i ⁱ			NORTH	···												
	, <u>5</u>	ι,		· 🏠	54 °	:								: ; ; `	1.1		1
1	19	.1	`!!		.:	MA	ODUCT I TERIAL: APE: DIS	NDFEB	N01,44	11							1
		;				DIN	AFE. DIS MENSION LERANC	N: 3/4″ E									
· ·		: 	1 I 1 I 1 I		÷,`	WE	IGHT(OZ ADE: N5	Z.): 0.24	:-1 		1			f.	:-1	i î C î	
':-	111		÷.		.1	ÇO	ATING: LL FORC	NICKEL		D MAGI	NETS		1. 1.	.1			
	.:		14. 14.	.1		MA	RFACE F GNETIZ	ATION [DIRECT	ION: TH	ROUGH	THICK	NĘSS	111			
1	.÷	*	1	PROPRIETAR	RY AND CONFIL	MA		ATING T	EMP(C	/F): 80/1					1	.:	
									P								