	1 1	i i i	1	1 1		1	1 1	1	111			111	1 1	i.				
ľ	ST	апгояс	o magr	ETS	, , ,	÷		, , ,	`;`	11		1			t i			1
1. 1 1. 1.	ţ.	:		<u>.</u>		100 10 100	:.:			10 - 1 1								1
						_ φ	DIMENS	ION: 3/4" [DIA. X 3/8"	' THICK								
	· * 2 · 2	: · · ·	1^{11}			1	· 1 2 · 1	1	111	· 1	\mathcal{L}^{\dagger}	111	с. 5 6 б	\mathcal{L}^{4}	1	· 3	; · !	
	: ÷	с 2 г	'a'	i'i		Ъ.		r T T	`;`			1					i. T	t.
	54	i di	.[ţ.i	j.i	.F	54	į.i		ţ.	i i	.]`				ţ.	;•i	
ci.		i.			NORTH	\							0		G		e st	
ſ	ei.	. :	'r'	11	· A	۰. ۲	:			зń.			e.			÷1		1
	11	, ii			;	.11	MA	DDUCT I TERIAL:	NDFEB	N0152	; · · ·		i i i	i.,	.[ţ	i	1
		11	···			;···	, DIN	SHAPE: DISC DIMENSION: 3/4" DIA. X 3/8" THICK WITH STEP IN TOLERANCES: ±0.004" X ±0.004"									e.	
1		i i i		÷		· ; ·		IGHT(OZ ADE: N4		r,				, , ,	1	11	i C C	1
E i F	<u>.</u>	11	.F	<u>.</u>	1.1 1			ATING: L FORC			D MAG	NETS		'			'	
n				• •			MA	RFACE F .GNETIZ. .GNETIC	ATION [DIRECT	ION: TH	ROUGH	THICK	NESS				
			: ¹	÷.,	PROPRIETAR	Y AND CONFI	MA		ATING T	remp(C	/F): 80/1		TANDARD M.		:	· · .		
ľ		i ci			: ¹		ļù	11			1 ^{1 1}	1 - 1 1 1 - 1	, ci	2 ¹	1 I I I I			