	1.1		111	1 1			7 T			T I		111	r r		1 1 1 L	1.1	î.	
	ST	апгояо	magn	ETS		<b>'</b> :.	. : :		<b>`</b> :.	2		1.	. : :		с Т.	.::	r i	:.
			:	:			:.:		;			;		.''		:.:		1
						φ	DIMENS	ION: 15/16	" DIA. X 2/	/10″ THIC	К							
	· 2 2 · 2	.*		· 1 • •	(	111	· 1 3 · 1	_1 <sup>1</sup> *	[n]	н. ў. 1	, i *	10	н в. С. в.	.2	11		e <sup>1 t</sup>	
	1		<b>`</b> :.			<b>`</b> 1.	, : : ;	T I	<b>`</b> £.			1.		<u>ک</u>	ь. Т.	.::		1.
	5.3	.''	:	÷	."	ł	1.1		1	5.7	.''			)		:.;		1
	- 1 - 1	.11	:		NORTH	\ /			i							: :	.11	
		. :	<b>`</b> 1.	.2	· 🏠	°н. Г			<b>`</b> 1.			1.		.4	1.	. :		1.
	51		1	1 - 1 - 1 - 1		:	MA	DDUCT I TERIAL:	NDFEB	N01.83	, <sup>, , ,</sup>		:.:	27		1.1		;
			;··			:	, DIN	APE: DIS IENSIOI LERANC	N: 15/16		X 2/10″ <sup>-</sup> ⊧0.004″	THICK	· · ·	.8	÷		.11	
	3	.4	<b>'</b> 11	.2	.4	<b>'</b> 1.	γWE	IGHT(OZ ADE: N4	Z.): 0,56			1.	.::	.4	ί.		, î L	1.
	ł.:		1	5.1		-	CO PUI	ATING: _L FORC	NICKEL E(LBS): 2	21.83		NETS	'			*		-
		.:	:**		.:	111	MA	RFACE F GNETIZ GNETIC	ATION I	DIRECT	ION: TH	ROUGH	THICK	NESS	;••		.1	
_	.1		14	.1							<b>/F): 80/1</b>				14		19	:
				1.1	, ''			, ' '			, ' '							