	a la		111	11			i i i		111	n i		1	i i			a la		
1	БТ	anford	Magr	IETS	:-1	•.··		r!	'r	. : : . : :	:-1	';·		11	'p	.::		1
	14		. E	.			` .;						·			•.;		1
						_ φ	DIMENS	ION: 1" DI	4. X 1/8″ TI	HICK								
		.4	;			11			111	2	ъ¢	;	c i c	2 ¹	11		e ¹	
1	s is	et.				F	11		1		et.	1	Č	\mathbf{y}^{sd}	1			11
	14		.T	. .;	,**		1 .]			1	."					*x [<i>.</i>	
	ai	.et	:	<u></u>	NORTH	1/										t	t	
e g	13	r:	1	. :	4	Р			191		ei.	ίţ.			1	. 2		11
	1			' .;	,	.T	_ MA	ODUCT I TERIAL: APE: DIS	NDFEB	N0192	, ¹¹		` .;	·''		'	.''	
	:	.4	;				, DIN		N: 1″ DIA		" THICK	111	.::	.el	1	:		
1	.11	r:	' !'				WE	IGHT(OZ ADE: N4	Z.): 0. <mark>4</mark> 3		et i			al i	ί.			11
	14	.''		×.;			CO		NICKEL		D MAGN	ETS					.**	ł
	e"		;···	a'	н 1 - 1	:	MA	RFACE F GNETIZ		DIRECT	601 ION: THR	OUGH	THICK	NESS	:**	a".		
		'	5 1	.1	PROPRIETAR						/F): 80/17 NG IS THE SOLE PRO				5 1			:
Î		e ^{cc}			, ¹¹				1 - 1 1 1 - 1					x ²³		1	energy and a second sec	