		1 1 1		1			1	111	τ	i i				111		i i	
ST	anford	Magn	ETS	· · 1	÷.				. :	· *	÷			с. с.		с. С. С. С.	1
Ч			÷.				.ie		1	, it						.ii	1.
					_φ	DIMENS	ION: 1 1/4'	' DIA. X 1 '	' THICK								
. :	.11	1. v			1 ¹¹	. 1		111	x - 1	, i f	1.1	, i	11	ļα.]	.÷:	
	i i i i	÷			÷		1 I 1 I	÷.	т. т. т.	· •	1.	Ċ		1.	. :	с. С.	1.
'þ	.b		<u>.</u>	, i i		'i)	, i j		1	,i:					' [-	,i j	
		:		NORTH	:			1							. 1		
	н н н н	÷		4	÷			1.			÷			÷		· · ·	١.
'þ.	.ii		ţ.	,÷	·1.	MA	ODUCT I TERIAL:	NDFEB	N0219	,i:		1	,i:		·	, i j	
.::	.8	;···			:	DIN	APE: DIS /IENSION LERANC	N: 1 1/4′				.4		;	.4	.41	
, , ,	 	÷1.	. :		Ξ.		IGHT(OZ ADE: N4			· · ·	÷			÷.	. :	i i C	1.
' <u> </u> .			÷.			CO	ATING: LL FORC	NICKEL		D MAG	NETS		;	···.		÷.	
	4	;				MA	RFACE F GNETIZ	ΑΤΙΟΝ [DIRECT	ION: TH	ROUGH	THICK	NESS	;		÷.,	
		Ч.,			Y AND CONFI	ΜA		ATING T	EMP(C	/F): 80/1				···,			
	, cr			.4	-	1.1	1 1 1			i i						The second secon	