



SAFETY DATA SHEET

Version 3.0 Revision Date 09/04/2017

1. PRODUCT AND COMPANY IDENTIFICATION

1.1Product identifiers

Product name

Lithium

Brand

SAM

CAS-No.

7439-93-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals. Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Stanford Advanced

Company

: Materials

23661 Birtcher Dr. Lake Forest, CA 92630

USA

Telephone

: +1 (949) 407-8904

Fax : +1 (949) 812-6690

1.4 Emergency telephone number

Emergency Phone #

: +1 (949) 407-8904

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Substances and mixtures, which in contact with water, emit flammable gases (Category 1), H260 Skin corrosion (Category 1B), H314

Serious eye damage (Category 1), H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word

Danger

Hazard statement(s)

iazaiu stateiii

H260

In contact with water releases flammable gases which may ignite

spontaneously.

H314

Causes severe skin burns and eye damage.

Precautionary statement(s)

P223

Keep away from any possible contact with water, because of violent

reaction and possible flash fire.

P231 + P232

Handle under inert gas. Protect from moisture.

P260

Do not breathe dust or mist.

P264

Wash skin thoroughly after handling.

P280

Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove P305 + P351 + P338 contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. P310 Specific treatment (see supplemental first aid instructions on this label). P321 P335 + P334 Brush off loose particles from skin. Immerse in cool water/ wrap in wet bandages. Wash contaminated clothing before reuse. P363 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. Store in a dry place. Store in a closed container. P402 + P404 P405 Store locked up. P501 Dispose of contents/ container to an approved waste disposal plant.

2.3Hazards not otherwise classified (HNOC) or not covered by GHS

Reacts violently with water.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1Substances

Formula : Li

Molecular Weight : 6.94 g/mol CAS-No. : 7439-93-2 EC-No. : 231-102-5 Index-No. : 003-001-00-4

Hazardous components

Componer	nt	. '	1.1	'	- '	Classification	Concentration
Lithium							
		: '	1		:'	Water-react. 1; Skin Corr. 1B; Eye Dam. 1; H260, H314	- :

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

In case of eve contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed no data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use approved class D extinguishers or smother with dry sand, dry ground limestone, or dry clay. Dry powder

Unsuitable extinguishing media

Do not use water, foam, or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Lithium oxides

5.3 Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

5.4 Further information

no data available

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Do not flush with water. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid formation of dust and aerosols.

Provide appropriate exhaust ventilation at places where dust is formed. Keep away from sources of ignition - No smoking.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Store under argon. Handle under argon. Keep container tightly closed in a dry and well-ventilated place. Never allow product to get in contact with water during storage.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL

PROTECTION 8.1 Control parameters

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum laver thickness: 0.11 mm Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method:

EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals. Flame retardant protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance Form: granular b) Odour no data available c) Odour Threshold no data available

d) Hq no data available

Melting point/freezing point

Melting point/range: 180 °C (356 °F) - lit.

Initial boiling point and boiling range

1,342 °C (2,448 °F) - lit.

Flash point g)

not applicable

h) Evapouration rate

no data available

i) Flammability (solid, gas) no data available

Upper/lower

no data available

flammability or

explosive limits

k) Vapour pressure 1 hPa (1 mmHg) at 723 °C (1,333 °F)

) Vapour density no data available

m) Relative density 0.534 g/mL at 25 °C (77 °F)

n) Water solubility no data available

o) Partition coefficient: n- no data available octanol/water

o) Auto-ignition no data available temperature

q) Decomposition no data available temperature

r) Viscosity no data available
s) Explosive properties no data available
t) Oxidizing properties no data available

9.2 Other safety information

no data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

no data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Reacts violently with water.

10.4 Conditions to avoid

Exposure to moisture.

10.5 Incompatible materials

Forms shock-sensitive mixtures with certain other materials., Iron and iron salts., Heavy metals, Phosphorus, Sulphur compounds, Oxygen, Nickel, Do not store near acids., Metals

10.6 Hazardous decomposition products

Other decomposition products - no data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

no data available

Inhalation: no data available

Dermal: no data available

LD50 Intraperitoneal - mouse - 1,000 mg/kg

Skin corrosion/irritation

no data available

Serious eye damage/eye irritation

no data available

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified

as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as

a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as

a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as

a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

no data available

no data available

Specific target organ toxicity - single exposure

no data available

Specific target organ toxicity - repeated exposure

no data available

Aspiration hazard

no data available

Additional Information

RTECS: OJ5540000

Large doses of lithium ion have caused dizziness and prostration, and can cause kidney damage if sodium intake is limited. Dehydration, weight loss, dermatological effects, and thyroid disturbances have been reported. Central nervous system effects that include slurred speech, blurred vision, sensory loss, ataxia, and convulsions may occur. Diarrhea, vomiting, and neuromuscular effects such as tremor, clonus, and hyperactive reflexes may occur as a result of repeated exposure to lithium ion., Cough, Shortness of breath, Headache, Nausea

12. ECOLOGICAL INFORMATION

12.1 Toxicity

no data available

12.2 Persistence and degradability

no data available

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

no data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1415 Class: 4.3

Proper shipping name: Lithium

Marine pollutant: No

Poison Inhalation Hazard: No.

IMDG

UN number: 1415

Class: 4.3

Packing group: I

Packing group: I

EMS-No: F-G, S-N

Proper shipping name: LITHIUM Marine pollutant: No

IATA

UN number: 1415

Class: 4.3

Packing group: I

Proper shipping name: Lithium

IATA Passenger: Not permitted for transport

15. REGULATORY INFORMATION

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Reactivity Hazard, Acute Health Hazard

Massachusetts Right To Know Components

						CAS-No.	Revision Date
Lithium			٠.		 ٠,	7439-93-2	 1993-04-24
1	1 1			1 1			
Pennsylv	ania Rigi	ht To Ki	now Com	nonents			

CAS-No. **Revision Date** 1993-04-24 7439-93-2

New Jersey Right To Know Components

CAS-No. **Revision Date** Lithium 7439-93-2 1993-04-24

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Eye Dam. Serious eve damage

H260 In contact with water releases flammable gases which may ignite spontaneously.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

Skin Corr. Skin corrosion

Substances and mixtures, which in contact with water, emit flammable gases Water-react.

HMIS Rating

Health hazard:

Chronic Health Hazard:

Flammability: Physical Hazard	:	3
NFPA Rating		
Health hazard:		3
Fire Hazard:		0
Reactivity Hazard:		2
Special hazard.l:		W

Further information

This material safety data sheet is offered solely for your information, consideration, and investigation. Stanford Advanced Materials provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein.